

That CAD Girl

Working with Land Desktop or Civil 3D Contours in IntelliCAD-based Carlson Programs

April 22, 2009

If you are working in an IntelliCAD version of Carlson Survey or Civil and need to bring in surface entities (contours) from a Civil 3D (C3D) or Land Desktop (LDT) drawing, it's actually very easy to do. However, it's not necessarily easy to find on your own. And, unfortunately, it's in a slightly different place depending on whether you're using the Carlson Survey or Civil menu.

FYI – If you simply try to “Open” a drawing that has AECC Contour Objects with an IntelliCAD-based program, it may look correct, but the entities will only be the dreaded “ACAD PROXY OBJECTS” that have bogus elevations. These are only

That CAD Girl

good to look at... not work with.

Whether you're using Survey or Civil, the only thing you'll need is a drawing file (DWG) containing the C3D or LDT contours for the surface. It doesn't even need to be opened, you just need to have it and be able to find it. (hey, I'm getting old!).

First, start a new drawing in Carlson.

Then, if you're using Carlson Civil:

1. Go to the "Surface" menu,
2. Select "Import/Export Surface"
3. Then, select "Convert LDT/Civil 3D Surface Drawing".

If you're using Carlson Survey:

1. Go to the "Surface" menu,
2. Select "Import/Export Surface Data"
3. Then, select "Convert Civil 3D Surface Drawing".

Next, you're prompted to "Select the LDT/Civil 3D Drawing to Read". After browsing to and selecting the LDT or C3D file, pick "Open".

That CAD Girl

Next, you're prompted to to "Select Converted Drawing to Write". This will be a new DWG file containing the converted data. After browsing to a new location and specifying a new file name, pick the "Save" button.

You'll see the conversion process in the text window. Once finished, you can open the converted drawing.

What you will find in the new drawing are all of the entities from the original LDT/C3D drawing except that any AECC Contour Objects have been converted to elevated PLINES and LINES.

The first step you'll probably want to take after opening the new drawing is to join together all of the contour PLINES and LINES. You may want to "Isolate" the layers for the contours first.

Then use the "Join Nearest" command under the "Edit" menu. Like most cases, make sure to have the "Join Only Common Elevations" and "Join Only Common Layers" options selected.

Originally posted on **Carlson Connection** by Jennifer Dibona

That CAD Girl

Engineering, Construction, and BIM

April 22, 2009

There have been many articles, discussions, and presentations on Building Information Modeling in the recent months. If you haven't already heard the basics, [this post covers it well](#). For surveyors, civil engineers, and construction firms, there are two things you should know about BIM and how it will impact your business.

First, BIM is very similar in its goals and processes to GIS. Basically, you are attaching data and other information to objects. This allows you to manage the facilities after they have been built and track their contents over time. This is very similar to how as-builts of infrastructure are managed and tracked through a GIS system. Water and storm sewer systems, telecomm transmission lines, and landscaping are types of things that are traditionally managed using

That CAD Girl

GIS. The information age has dramatically opened up opportunities for professionals to gather, collate, and attach data to their surveys, designs, and as-builts.

Secondly, since buildings are not constructed in isolation, they must tie into the site grading and infrastructure, further opportunities for designers and contractors have opened up. Complex site plans showing how the grading, structural design, and utilities will all connect are now possible, and represent a new deliverable for firms to offer their clients. Carlson Software offers many solutions for creating these models and because Carlson data migrates well between various CAD and GIS platforms, owners and developers of these projects can be assured that their designs will be ready for management once construction is complete.

Originally posted on **Carlson Connection** by Felicia Provencal

That CAD Girl

Carlson + ESRI = Wow!

April 22, 2009

[So, how cool is this?](#)

At the [Carlson User Conference](#) this week in Lexington, KY, Brent Jones of [ESRI](#) announced a new grant program in coordination with Carlson Software. The program will bring ESRI products to every IntelliCAD-based Carlson program.

Speaking with Brent on Tuesday, he said that a few of the details have yet to be worked out, but Carlson IntelliCAD users should be hearing details in about a month.

Originally posted on **Carlson Connection** by Jennifer Dibona

That CAD Girl

How Does Carlson Support Their Users? Ask David Farina

April 22, 2009

I'm going to post a LONG email stream between one of my clients, David Farina, Bruce Carlson and Dave Carlson. You can see the new feature that David requested and Bruce and Dave's responses. David received a "development" version of the new features approximately a week after submitting this request.

I asked him for a statement describing his experience with Carlson:

Recently I found that the Time of Concentration input boxes were inadequate under the hydrology portion of Carlson Civil Suite so I emailed a description of the problem to them. I was very impressed to get a phone call the same day. They discussed the problem with me and had a revised program update to me in under a week. I've been emailing

That CAD Girl

Autodesk for over a year on problems with Civil 3D and never heard a peep. Needless to say I'm very happy with the customer service I have received from Carlson thus far.

Here is the original question from David Farina on March 4, 2009:

Jennifer,

I was going through a mock project to learn the hydrology part of Carlson and noticed a critical deficiency in Time of Concentration input. The review agencies around here want to see the TR-55 method. First, the TR 55 minimum sheet flow needs to be 100' instead of 300'. They recently changed it per the TR-55 Web site. Second, I don't think I've ever had a project where you didn't have to split one of these flow types into 2 or more mannings roughness areas.

For example: a flow path that starts on dense grass for 50' then passes over asphalt for 75' and back to grass for 200' would need to be calculated as follows:

Sheet flow 50' Grass -> Sheet flow 50' Asphalt -> Shallow

That CAD Girl

Concentrated flow 25' Paved -> Shallow Concentrated flow 200' UnPaved.

But as you can see the Carlson input only allows for one entry per flow type.

Time of Concentration (TR-55)

Select Flow Line From Screen

Sheet Flow | Shallow Concentrated Flow | Channel Flow

Manning's n: 0.240 [Select]

Two-yr 24-hr Rainfall: 3.59 in

Flow Length: 100.00 ft

Land Slope: 2.00 %

Time of Concentration: 0.225 hr
13.473 min

Total Time of Concentration: 0.252 hrs, 15.1 mins

[Calculate] [Report] [Clear] [Exit] [Help]

That CAD Girl

Time of Concentration (TR-55)

Select Flow Line From Screen

Sheet Flow | **Shallow Concentrated Flow** | Channel Flow

Surface Description

☐ Paved ☒ Unpaved

Flow Length: 225.00 ft

Land Slope: 2.00 %

Time of Concentration: 0.027 hr
1.643 min

Total Time of Concentration: 0.252 hrs, 15.1 mins

Calculate Report Clear Exit Help

Below is the Intellisolve version: Notice the A, B C

That CAD Girl

TR-55 Tc Worksheet

	A	B	C
Manning's n-value	0.24	0.011	0.011
Flow length (ft, 300 max.) =	50	50	
Two-yr 24-hr rain (in)	3.59	3.59	
Land slope (%)	2	2	
Sheet flow time	7.74	0.66	0.00

Shallow Concentrated Flow

	A	B	C
Flow length (ft)	25	200	
Watercourse slope (%)	2	2	
Surface description	Paved	Unpaved	Paved
Shallow conc. flow time ..	0.14	1.46	0.00

Channel Flow

	A	B	C
X-sectional area (sqft) =			
Wetted perimeter (ft) =			
Channel slope (%)			
Manning's n-value ...	0.015	0.015	0.015
Flow length (ft)			
Channel flow time	0.00	0.00	0.00

Sheet flow time = 8.40 min
Shallow conc. flow time = 1.61 min
Channel flow time = 0.00 min
Time of conc., Tc = 10.0 min

Compute Print... Help Exit

There is a 5.1 minute difference in TC results which results in a 2 CFS difference in the 100yr example below:

That CAD Girl

Runoff Hydrograph - SCS Method

Method: SCS Triangular

SubBasin

Area Units: ☐ Sq Ft ☐ Sq Miles ☒ Acres

Drainage Area: 1.8498968

Runoff Curve Number: 83.00

Time of Concentration: 0.17 hr

Base Flow: 0.00 cfs

Antecedent Moisture Condition: ☐ 1 ☐ 2 ☒ 3

Rainfall

Storm Type: II - 24hr

Return Period: 100 Year

Rainfall Depth: 9.43 in

Time Increment: 0.03 hr

Peak Attenuation Factor: 484

Calculation

Peak Discharge	18.46	cfs
Time to Peak	12.07	hr
Volume	1.29	acre-ft

Runoff Hydrograph - SCS Method

Method: SCS Triangular

SubBasin

Area Units: ☐ Sq Ft ☐ Sq Miles ☒ Acres

Drainage Area: 1.8498968

Runoff Curve Number: 83.00

Time of Concentration: 0.25 hr

Base Flow: 0.00 cfs

Antecedent Moisture Condition: ☐ 1 ☐ 2 ☒ 3

Rainfall

Storm Type: II - 24hr

Return Period: 100 Year

Rainfall Depth: 9.43 in

Time Increment: 0.03 hr

Peak Attenuation Factor: 484

Calculation

Peak Discharge	16.39	cfs
Time to Peak	12.10	hr
Volume	1.31	acre-ft


That CAD Girl

If the above example is that different then I am also concerned about how the Time to inlet is calculated in the example below:

The screenshot shows a software interface with a top navigation bar containing buttons for 'Settings', 'Design', 'Analyze', and 'Analyze by Hydra'. Below this is a 'Structure Actions' section with 'Add', 'Edit', and 'Remove' buttons. A tabbed interface below shows 'Structure', 'Drainage' (selected), 'Pipe', and 'Hydraulic Calc'. The 'Drainage' tab contains the following fields and controls:

- 'Current Structure:' with a text box containing 'M1'.
- 'Input Type' with a dropdown menu set to 'Drainage Data'.
- 'Area Units' section with three radio buttons: 'Sq Ft', 'Sq Mile', and 'Acre' (which is selected).
- A 'Draw' button.
- 'Drainage Area' with a text box containing '1.3721', a 'Pick' button, and a 'Calc' button.
- 'Time to Inlet' with a text box containing '7.1' and a unit dropdown set to 'min'.
- 'Curve Number' with a text box containing '83' and a 'Select' button.
- 'Pond/Swamp Adjust' with a text box containing '1.0000'.
- 'Known Flow' with a text box containing '0.0000', a unit dropdown set to 'cfs', and a 'Thru Inlet' checkbox.
- 'In Hydrograph' with a text box and a 'Select' button.

That CAD Girl



Time of Concentration (SCS)

Input values

Select CN from Table

Curve Number: 83

Length of Flow (ft): 412.10

Average Land Slope (%): 3.59

Select Flow Line from Screen

Output values

Time of Concentration: 0.125 hrs, 7.5 mins

Calculate Report Exit Help

Was the SCS method used to get the 7.1 min value?

Notice the 7.5 value in the TC dialog to the right.

This was the value if I SELECT FLOW LINE FROM SCREEN and pick the path that the dialog on the left generates.

Can I generate a report of how the time to inlet was calculated?

Maybe there can be a button next to the Time to inlet to select TR-55

That CAD Girl

Maybe Mannings coefficients can also be put into the WATERSHED->DEFINE RUNOFF LAYERS to be used for this calc as the flow path passes through each polyline area the same way Carlson already calculates the composite CN.



Define Runoff Layers - C:\...R17.2\User\Wn_layer.dta

Hydro Method: ☐ Rational Method ☒ SCS Method

Layer	Type of Area	Runoff Curve Number
B-CONC	Paved Lots Roofs & Driveways, Soil Type B	98
B-FP	Paved Lots Roofs & Driveways, Soil Type B	98
P-Border	Open Space-Good (>75% grass), Soil Type B	61

Default Area Type: Default Runoff Curve Number:

Will any of this matter if we get HydroCAD and link it to Carlson?

Just food for thought.

That CAD Girl

Thank You,

David Farina

Senior Designer

I forwarded David's question onto Bruce Carlson, President of Carlson Software, and Dave Carlson, Director of Programming, and received this response from Bruce:

Folks: Excellent input—this will find its way into the next release for sure. We've spent a lot of time studying Haested and matching numbers there on pipe flows in culverts, for example, covering all conditions—but do need to put to bed Time of Concentration for approved defaults and sub-catchment conditions as they vary within a watershed area. This Intellisolve example is really helpful. Also, I took in input at Jennifer's Statesville, NC presentation Dec. 2007 that mentioned the new 100' default and also mentioned:

Using $Q=CIA$, there are new "rules" being published that

That CAD Girl

*using larger pipes or it may be larger drainage areas, there is an added multiplier in the form $Q=CIA*Q1$ where $Q1$ is a table of values. I didn't get the full details, but we need to research this.*

And in storm sewer design, if we are compositing the calc of time to inlet using a "short-form" SCS-style method, based on percentage area of various land uses and associated runoff coefficients, we need to have a Report button that documents the results for full vetting and reporting out by users, and we need to incorporate an additional auto-calculated, long-form TR55 time of concentration there as well that uses sheet flow, channel flow and shallow concentrated flow. One key in all this is to be able to auto-distinguish these flow types from the DTM and land uses and have the forms filled out with default values, which the user can change.

Question I'm curious about. Say you built a gentle 6'wide, 1% slope swale with 6:1 side slopes, hardly noticeable, mowable, between lots in a subdivision. Would the flow in that be treated as shallow concentrated flow or channel flow? When would one condition end and another

That CAD Girl

begin, by definition, so we can get real precise on auto-calculating these using layers/land use types and DTM values?

Good stuff, and it will get done.

Bruce Carlson, PE

Pres., Carlson Software

David added the following:

I think when to use channel flow should be determined by the width of the bottom of the channel and hence how deep the channel gets on an 2yr storm 24 storm.

You could have a channel with 1:1 side slopes but if the bottom was 50' wide and the flow path started in the channel then

the first 100' would still be sheet flow in my book. Unless of course a huge amount of water was entering the channel from another basin.

I think the concentrated and channel flow times (being in

That CAD Girl

the fraction of a minute range) are so small and have such a small impact on overall time

compared to sheet flow (fraction of an hour) that you could pick an arbitrary number like 5' wide bottom and smaller is channel flow and not upset the model.

Sheet flow probably makes up 80 to 90 % of overall TC if it is over grass.

Anyone disagree?

Thank You

Dave Carlson sent this on March 11, 2009

Hi David,

Here's an update to the Tc by TR-55 routine that allows unlimited number of breakouts. This update is for Carlson 2009 on Acad 2007-09. To install, unzip and copy the arx to

That CAD Girl

the Carlson2009LSP folder. Let me know if you need a different version or have more suggestions.

For the Storm Sewer Network routine, I put it on the to-do list to add a Select button next to the Tc to show the components that make up the Tc like the Select button does for CN. Also we will look at adding Manning's n to the Define Runoff Layers for use with Tc calcs.

Thanks for the input.

Dave

Originally posted on **Carlson Connection** by Jennifer Dibona

Coming in Carlson 2010

April 22, 2009

I'm not privy to the "official" list of coming updates, but I can share a few things that I know will be in the next

That CAD Girl

release. Most of these come from “wishlist” items I have submitted on behalf of my clients.

The folks at Carlson are welcome to add their 2-cents in the Comments of this post or on Direct From Carlson.

Option for placing building footprint a distance off the building setback line.

Currently, the LotNet command places the building footprint exactly on the midpoint of the building setback line. We heard the request several times to have the option of placing the footprint some distance behind the setback line. It will be in the 2010 release.

C & G Survey

Instead of having two separate survey programs, Carlson will be incorporating C & G as a separate set of menus in Carlson Survey in 2010.

Basic IntelliCAD Menu

If you’re running Carlson on top of an AutoCAD-based program, you have an icon or menu option to switch over to an AutoCAD

That CAD Girl

menu that has basic Draw commands such as line, pline and text and basic Modify commands such as copy, explode and pedit. Although it's not easy to get to right now, IntelliCAD has a similar set of menus and toolbars. Carlson 2010 stand-alone with IntelliCAD will have a menu item and toolbar icon allowing you to easily switch over to the IntelliCAD menus and then back again to the Carlson menus.

Lookup table of curb slopes for super-elevation transitioning

This new feature will handle curb transitions like those shown in this [NC DOT detail drawing](#).

Originally posted on **Carlson Connection** by Jennifer Dibona

Poll Question 3/30/2009

April 22, 2009

[polldaddy poll=1493826]

Originally posted on **Carlson Connection** by Jennifer Dibona